

#### **Section 1. Product and Company Identification**

Manufacturer : Seacoat SCT, LLC

31902 Industrial Park Dr., Pinehurst, Texas, USA. 77362 USA

Tel: 832-237-4400; Fax: 832-237-4414

Material Name : Sea-Speed V 10X Ultra – Clear (Part A) Activator

**MSDS No.** : 042017ASSV10CLR-A

CAS No. : N/A - Mixture

#### Section 2. Hazards Identification

**Emergency overview** 

Form : Liquid

Color : clear to slightly yellow

Odor : Amine like

Symbols :

! AT

**Statements** : May cause eye tissue damage

Harmful or fatal if Swallowed

**Potential Health affects** 

Eye Contact : Irritating. May cause eye tissue damage if not removed quickly

Skin Contact : Moderately irritating

**Inhalation** : May cause respiratory tract irritation

**Ingestion**: May cause irritation to mouth, throat and stomach

### **Section 3. Composition Information**

**HAZARDOUS Ingredients** 

**Dibutyltin Dineodecanoate** : CAS No.251168-22-3 < 5% **3-Aminopropyltriethoxy** : CAS No.919-30-2 < 10%

silane

#### **Section 4. First Aid Measures**

Skin Contact : Wash with soap and water for at least 10 minutes. Remove

contaminated clothing and wash thoroughly before re-use. Consult a

doctor if skin irritation persists.

**Inhalation**: If breathing difficulty occurs remove affected person out into fresh air.

Consult a physician if nose, throat or eye irritation persists.

Eye Contact : Rinse eyes thoroughly with fresh water for ten minutes. Use eye rinse

solution. If irritation persists, contact an ophthalmologist.



## Material Safety Data Sheets SEA-SPEED V10X ULTRA – CLEAR

Part A (Activator)

Rinse mouth thoroughly with water. Do not induce Vomiting. Give Ingestion

plenty of fluids (water). If discomfort persists, contact a physician.

Notes to Physician If substance is ingested in large amounts, apply therapy for chemical

burn. Early endoscopy in order to assess mucosa lesions in the esophagus and stomach. If needed, aspirate left over substance.

## **Section 5. Fire Fighting Measures**

Flash point > 100°C (TCC) Auto ignition temperature Not determined : Not determined Lower Explosive limit % Not determined

**Upper Explosive Limit %** Foam, CO2, dry powder. Reacts with water and hydrolysis is Suitable extinguishing

media exothermic.

Specific hazards during NOx from fire and fumes

firefighting Special protective

For fire fighters

: As in any fire, self contained positive pressure breathing apparatus, equipment (MSHA,NIOSH) or approved equivalent and full protective gear.

#### Section 6. Accidental Release Measures

Personal Ensure proper ventilation. Avoid contact with skin and eyes.

**Environmental** Follow local, state, federal and or provincial laws and regulations. Do

not contaminate groundwater, soil streams, ponds or lakes.

Methods for cleanup Use absorbent materials such as universal binder, saw dust, sand or

other appropriate material. Place in marked container and sealed container for disposal in accordance with existing regulations.

### Section 7. Handling and Storage

Handling Use in well ventilated areas. Avoid direct skin and eye contact. Avoid

breathing fumes or mist. Wash hands with soap and water after

handling.

Storage store between 5°C - 38°C (40°F - 100°F)

### **Section 8. Exposure Controls / Personal Protection**

Engineering controls Provide good ventilation in confined areas. Eye & face protection Wear safety glasses with side shields.

Butyl rubber. Wear protective gear as needed. Hand protection



## Material Safety Data Sheets SEA-SPEED V10X ULTRA – CLEAR

Part A (Activator)

**Respiratory protection**: Wear a NIOSH/MSHA approved respirator during application whenever

workplace conditions warrant respirator use.

**Hygiene measures** : Avoid contact with skin, eyes and or clothing. Do not inhale vapors or

mist. Do not eat, drink or smoke while using this product. Remove

contaminated clothing and thoroughly wash before re-use

# Section 9. Physical and Chemical Properties

**Appearance** 

Form : Liquid

Color : Colorless to yellow

Odor : Pungent

**Safety Data** 

PH : Not determined

Flash point : > 100°C

Melting point: Not determinedBoiling Point: Not determinedEvaporation rate: <1 ( n-BuAC=1)</th>Flammability limits in air: Not determined

**Auto ignition Temperature** : > 300°C **Vapor density** : >1 Air =1

**VOC Mixed A & B** : 21.8 gr/Liter incl water and exempt compounds

#### Section 10. Stability and Reactivity

Hazardous decomposition

products

Ethanol in case of hydrolysis

**Hazard reactions**: No dangerous reactions known

**Additional information**: Incompatibility with humidity, water, alkalis, acids.

# Section 11. Toxicological Information

Sensitization : Possibility of skin sensitization may occur under prolonged exposure

Carcinogenicity : None

**Genotoxicity** : Not mutagenic

**Toxicity to reproduction**: No evidence of effects of reproductive/developmental toxicity.

Notes : Prolonged exposure to spray mists can cause dizziness, nausea,

headaches and be irritating to the eyes, respiratory tract and skin.

Ingestion may cause gastrointestinal irritation or damage.



### **Section 12. Ecological Information**

The data we have available at our disposal does not necessitate identification as an environmentally hazardous substance. An environmental hazard may be considered due to unprofessional handling and or disposal.

**Bioaccumulation**: Not bioaccumulative

#### **Section 13. Waste Disposal**

**Disposal method**: PART A in its individual state may be a hazardous waste when

discarded or disposed of according to Federal regulations (40CFR 261.4 (b) (4). Under RCRA, it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Do not allow this material into sewers and water supplies. Waste must be disposed of in accordance

with Federal, state and local regulations.

Advice on disposal : Mix all residual part A with Part B and allow it to cure fully in an open

container. Cured product may be disposed of as a non-hazardous

solid waste.

#### **Section 14. Transport Information**

**Department of Transportation (DOT)** 

UN 3267 : CORROSIVE LIQUID

BASIC, ORGANIC, N.O.S. (3-aminopropyl-triethoxysilane)

Transport hazard Class : 8
Packing group : ||
Environmental Hazard : --

Air Transport (ICAO-TI/IATA -DGR)

UN 3267 : CORROSIVE LIQUID

BASIC, ORGANIC, N.O.S. (3-aminopropyltriethoxysilane)

Transport hazard class : 8
Packing Group : ||
Environmental hazard : -Special precautions for use : Yes

IATA-C : EGR Code 8L IATA-P : EGR Code 8L

**SEA TRANSPORT (IMDG)** 

UN 3267 : CORROSIVE LIQUID

BASIC ORGANIC N.O.S. (3-aminopropyltriethoxysilane)

Transport hazard class : 8
Packing Group : ||
Environmental hazard : --

(Marine Pollutant)

**Special precautions for use** : Yes **EmS** F-A, S-B



#### **Section 15. Regulatory Information**

OSHA Clean air act (112) : None listed CERCLA reportable : None listed

quantities

**SARA TITLE III (311/312)** 

Fire : No
Pressure : No
Reactivity : No
Acute : No
Chronic : No

SARA TITLE III (313) : Xylene (mixed Isomers), standard reporting threshold.

TSCA : None listed California Proposition 65 : None listed

International Chemical

Inventory

USA (TSCA) : Yes
Canada (DSL) : Yes
Australia (AICS) : Yes
New Zealand (NZIoC) : Yes
Europe (EINECS) : Yes
Japan (MITI) : Yes
Korea (TCCL) : Yes
China : Yes

#### **Section 16. Other Information**

Key to abbreviations

**CERCLA** Comprehensive Environmental Response, Compensation, and Liability Act **EGR** : **EmS** IATA-DGR The International Air Transport Association - Dangerous Goods Regulations **ICAO-TI** International Civil Aviation Organisation - Technical Instructions **IMDG** The International Maritime Dangerous Goods **MSDS** Material Safety Data Sheet **MSHA** Mine Safety and Health Administration **NIOSH** National Institute for Occupational Safety and Health **NOx** Nitrogen Oxide **OSHA** Occupational Safety and Health Administration TCC Tag Closed Cup **TSCA Toxic Substances Control Act** VOC Volatile Organic Compound



#### Manufacturer disclaimer

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Seacoat SCT, LLC or SEA-SPEED-PC, LLC assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. SEACOAT SCT,LLC and SEA-SPEED-PC, LLC EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF SEACOAT SCT,LLC and SEA-SPEED-PC, LLC ARE AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product and does not imply that similar products could not be used. Seacoat SCT, LLC reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

~~ We have your bottom covered ~~